



digital scroll compressor



Modelo / Model	R407C	XWP-2200DG	XWP-2800DG	XWP-3600DG	XWP-4500DG	XWP-5600DG
Código SAP - SAP code		190002886	190002887	190002888	190002889	190002890
Alimentación - Power supply	W/Hz/Ph	220/50/1	220/50/1	220/50/1	220/50/1	220/50/1
Capacidad Frigorífica - Cooling capacity	kW	2,2	2,8	3,6	4,5	5,6
Capacidad calorífica - Heating capacity	kW	2,5	3,2	4	5	6,3
Absorción de potencia - Max input consumer	W	140	140	140	140	140
Caudal de aire - Air flow volume	m³/h	560	560	560	670	670
Nivel sonoro - Sound level	dB (A)	36	36	36	46	46
Tipo de conexión - Connector type		aborcardado- flaring nut	aborcardado- flaring nut	aborcardado- flaring nut	aborcardado- flaring nut	aborcardado- flaring nut
Conexión tubo líquido - Liquid line pipe	Ø mm / inch	9,53-3/8"	9,53-3/8"	9,53-3/8"	9,53-3/8"	9,53-3/8"
Conexión tubo gas - Gas line pipe	Ø mm / inch	16 - 5/8"	16 - 5/8"	16 - 5/8"	19 - 3/4"	19 - 3/4"
Peso neto - Net weight	kg	11	11	11	17	17
Dimensiones - Dimensions	l/v/p - l/h/d mm	880x280x210	880x280x210	880x280x210	1080x330x222	1080x330x222

CONDICIONES DE PRUEBA - TEST CONDITIONS

Capacidad Frigorífica*: Temp. Externa 35°C / Interna 27°C B.S./19°C B.U
Cooling Capacity*: External Temp. 35°C / Internal 27°C D.B. / 19°C W.B.

Capacidad calorífica: Temp. Interna 21°C / Externa 7°C B.S./6°C B.U.**
Heating Capacity**: Internal Temp. 21°C / External 7°C D.B. / 6°C W.B.