



# Unidad suelo/techo

Floor/ceiling type

**XIDEKO**  
air for life



CE

digital scroll compressor

Modelo / Model	R407C	XFC-3.6M2RB7-B	XFC-4.5M2RB7-B	XFC-5.6M2RB7-B	XFC-7.1M2RB7-B	XFC-8M2RB7-B	XFC-9M2RB7-B	XFC-11.2M2RB7-B
Código SAP - SAP code		190005414	190005415	190005416	190005417	190005421	190005422	190005423
Alimentación - Power supply	V/Hz/Ph	220/50/1	220/50/1	220/50/1	220/50/1	220/50/1	220/50/1	220/50/1
Capacidad Frigorífica - Cooling capacity	kW	3,6	4,5	5,6	7,1	8	9	11,2
Capacidad calorífica - Heating capacity	kW	4	5	6,3	8	9	10	12,5
Absorción de potencia - Max input consumption	W	170	170	170	170	170	170	170
Caudal de aire - Air flow volume	m <sup>3</sup> /h	800	800	800	1000	1200	1200	1400
Nivel sonoro - Sound level	dB (A)	36	36	38	40	40	41	41
Tipo de conexión - Connector type		anillo/dado - ring nut	anillo/dado - ring nut	anillo/dado - ring nut	anillo/dado - ring nut	anillo/dado - ring nut	anillo/dado - ring nut	anillo/dado - ring nut
Conexión tubo líquido - Liquid line pipe	Ø mm / inch	9,53 - 3/8"	9,53 - 3/8"	9,53 - 3/8"	9,53 - 3/8"	9,53 - 3/8"	9,53 - 3/8"	9,53 - 3/8"
Conexión tubo gas - Gas line pipe	Ø mm / inch	19,10 - 3/4"	19,10 - 3/4"	19,10 - 3/4"	19,10 - 3/4"	19,10 - 3/4"	19,10 - 3/4"	19,10 - 3/4"
Peso neto - Net weight	kg	28	28	28	32	32	32	32
Dimensiones - Dimensions	V/h/p - Vh/d mm	990x620x220	990x620x220	990x620x220	1200x620x220	1200x620x220	1200x620x220	1200x620x220

### CONDICIONES DE PRUEBA - TEST CONDITIONS

Capacidad Frigorífica\*: Temp. Externa 35°C / Interna 27°C B.S./19°C B.U.  
Cooling Capacity\*: External Temp. 35°C / Internal 27°C D.B. / 19°C W.B.

Capacidad calorífica\*\*: Temp. Interna 21°C / Externa 7°C B.S./6°C B.U.  
Heating Capacity\*\*: Internal Temp. 21°C / External 7°C D.B. / 6°C W.B.