



digital scroll compressor



Modelo / Model	R407C	XC4-2800D2	XC4-3600D2	XC4-4500D2	XC4-5600D2	XC4-7100D2	XC4-8000D2	XC4-9000D2	XC4-11200D2
Código SAP - SAP code		190003516	190003517	190003518	190001343	190001344	190001345	190001346	190001347
Alimentación - Power supply	W/Hz/Ph	220/50/1	220/50/1	220/50/1	220/50/1	220/50/1	220/50/1	220/50/1	220/50/1
Capacidad Frigorífica - Cooling capacity	kW	2,8	3,6	4,5	5,6	7,1	8	9	11,2
Capacidad calorífica - Heating capacity	kW	3,2	4	5	6,3	8	9	10	12,5
Absorción de potencia - Max input consumer	W	170	170	170	170	170	170	170	170
Caudal de aire - Air flow volume	m ³ /h	870	870	1010	1010	1200	1200	1320	1860
Nivel sonoro - Sound level	dB (A)	35	35	38	38	42	42	44	44
Tipo de conexión - Connector type		abovedado- ang.u.	abovedado- ang.u.	abovedado- ang.u.	abovedado- ang.u.	abovedado- ang.u.	abovedado- ang.u.	abovedado- ang.u.	abovedado- ang.u.
Conexión tubo líquido - Liquid line pipe	Ø mm / inch	9,53 - 3/8"	9,53 - 3/8"	9,53 - 3/8"	9,53 - 3/8"	9,53 - 3/8"	9,53 - 3/8"	9,53 - 3/8"	9,53 - 3/8"
Conexión tubo gas - Gas line pipe	Ø mm / inch	19,10 - 3/4"	19,10 - 3/4"	19,10 - 3/4"	19,10 - 3/4"	19,10 - 3/4"	19,10 - 3/4"	19,10 - 3/4"	19,10 - 3/4"
Peso neto - Net weight	kg	22	22	25	25	25	25	45	45
Dimensiones - Dimensions	l/h/p - l/h/d mm	840/240/840	840/240/840	840/240/840	840/240/840	840/240/840	840/240/840	840/240/840	840/240/840
Dimensiones - Dimensions	l/h/p - l/h/d mm	950/40/950	950/40/950	950/40/950	950/40/950	950/40/950	950/40/950	950/40/950	950/40/950

CONDICIONES DE PRUEBA - TEST CONDITIONS

Capacidad Frigorífica*: Temp. Externa 35°C / Interna 27°C B.S./19°C B.U.
Cooling Capacity*: External Temp. 35°C / Internal 27°C D.B. / 19°C W.B.

Capacidad calorífica**: Temp. Interna 21°C / Externa 7°C B.S./6°C B.U.
Heating Capacity**: Internal Temp. 21°C / External 7°C D.B. / 6°C W.B.