



Cassette 1 via

One-way cassette



Disponibilidad limitada - Limited availability

CONTATTARE UFFICIO COMMERCIALE
CONTACT SALES DEPARTMENT



digital scroll compressor

Modelo / Model	R407C	XC1-2800D	XC1-3600D	XC1-4500D	XC1-5600D	XC1-7100D
Código SAP - SAP code		190001335	190001336	190001337	190001338	190001339
Alimentación - Power supply	V/Hz/Ph	220/50/1	220/50/1	220/50/1	220/50/1	220/50/1
Capacidad Frigorífica - Cooling capacity	kW	2,8	3,6	4,5	5,6	7,1
Capacidad calorífica - Heating capacity	kW	3,2	4	5	6,3	8
Absorción de potencia - Max input consumption	W	170	170	170	170	170
Caudal de aire - Air flow volume	m ³ /h	470	500	780	780	1080
Nivel sonoro - Sound level	dB (A)	38	38	42	42	42
Tipo de conexión - Connector type		american- flaring nut	american- flaring nut	american- flaring nut	american- flaring nut	american- flaring nut
Conexión tubo líquido - Liquid line pipe	Ø mm / inch	9,53 - 3/8"	9,53 - 3/8"	9,53 - 3/8"	9,53 - 3/8"	9,53 - 3/8"
Conexión tubo gas - Gas line pipe	Ø mm / inch	19,10 - 3/4"	19,10 - 3/4"	19,10 - 3/4"	19,10 - 3/4"	19,10 - 3/4"
Peso neto - Net weight	kg	23	23	31	31	31
Dimensiones - Dimensions	V/hp - Vh/d mm	850/235/400	850/235/400	1200/198/655	1200/198/655	1200/198/655
Dimensiones - Dimensions	V/hp - Vh/d mm	1050/18/470	1050/18/470	1420/10/755	1420/10/755	1420/10/755

CONDICIONES DE PRUEBA - TEST CONDITIONS

Capacidad Frigorífica*: Temp. Externa 35°C / Interna 27°C B.S./19°C B.U.
Cooling Capacity*: External Temp. 35°C / Internal 27°C D.B. / 19°C W.B.

Capacidad calorífica**: Temp. Interna 21°C / Externa 7°C B.S./6°C B.U.
Heating Capacity**: Internal Temp. 21°C / External 7°C D.B. / 6°C W.B.