



**digital scroll compressor**



Modelo / Model	R410A	XC4-2.8M2RC6-BB	XC4-3.6M2RC6-BB	XC4-4.5M2RC6-BB	XC4-5.6M2RC6-AA	XC4-7.1M2RC6-AA	XC4-8M2RC6-AA	XC4-9M2RC6-AA	XC4-11.2M2RC6-AA
Código SAP - SAP code		190005316	190005386	190005387	190005317	190005388	190005389	190005318	190005390
Alimentación - Power supply	W/Hz/Ph	220/50/1	220/50/1	220/50/1	220/50/1	220/50/1	220/50/1	220/50/1	220/50/1
Capacidad Frigorífica - Cooling capacity	kW	2,8	3,6	4,5	5,6	7,1	8	9	11,2
Capacidad calorífica - Heating capacity	kW	3,2	4	5	6,3	8	9	10	12,5
Absorción de potencia - Max input consumer	W	170	170	170	170	170	170	170	170
Caudal de aire - Air flow volume	m³/h	870	870	1010	1010	1200	1200	1320	1860
Nivel sonoro - Sound level	dB (A)	36	36	38	38	42	42	44	44
Tipo de conexión - Connector type		abovedado-ángulo	abovedado-ángulo	abovedado-ángulo	abovedado-ángulo	abovedado-ángulo	abovedado-ángulo	abovedado-ángulo	abovedado-ángulo
Conexión tubo líquido - Liquid line pipe	Ø mm / inch	6,35 - 1/4"	6,35 - 1/4"	6,35 - 1/4"	9,53 - 3/8"	9,53 - 3/8"	9,53 - 3/8"	9,53 - 3/8"	9,53 - 3/8"
Conexión tubo gas - Gas line pipe	Ø mm / inch	12,7 - 1/2"	12,7 - 1/2"	12,7 - 1/2"	16, - 5/8"	16, - 5/8"	16, - 5/8"	16, - 5/8"	16, - 5/8"
Peso neto - Net weight	kg	22	22	22	28	28	28	35	35
Dimensiones - Dimensions	l/h/p - l/h/d mm	580/254/580	580/254/580	580/254/580	840/240/840	840/240/840	840/240/840	840/310/840	840/310/840
Dimensiones - Dimensions	l/h/p - l/h/d mm	650/30/650	650/30/650	650/30/650	950/40/950	950/40/950	950/40/950	950/40/950	950/40/950

**CONDICIONES DE PRUEBA - TEST CONDITIONS**

Capacidad Frigorífica\*: Temp. Externa 35°C / Interna 27°C B.S./19°C B.U.  
Cooling Capacity\*: External Temp. 35°C / Internal 27°C D.B. / 19°C W.B.

Capacidad calorífica\*\*: Temp. Interna 21°C / Externa 7°C B.S./6°C B.U.  
Heating Capacity\*\*: Internal Temp. 21°C / External 7°C D.B. / 6°C W.B.