



# Unidad de conducto

Ducted type

**XIDEKO**  
air for life



CE

digital scroll compressor

Modelo / Model	R410A	XDC-4.5M2 RC6	XDC-5.6M2 RC6	XDC-7.1M2 RC6	XDC-8M2 RC6	XDC-9M2 RC6	XDC-11.2M2 RC6	XDC-14M2 RC6
Código SAP - SAP code		190005397	190005398	190005399	190005400	190005401	190005402	190005403
Alimentación - Power supply	V/Hz/Ph	220/50/1	220/50/1	220/50/1	220/50/1	220/50/1	220/50/1	220/50/1
Capacidad Frigorífica - Cooling capacity	kW	4,5	5,6	7,1	8	9	11,2	14
Capacidad calorífica - Heating capacity	kW	5	6,3	8	9	10	12,5	16
Absorción de potencia - Max input consumer	W	200	200	335	335	380	380	380
Caudal de aire - Air flow volume	m <sup>3</sup> /h	840	840	1140	1140	1320	1680	2040
Nivel sonoro - Sound level	dB (A)	40	40	40	40	70	70	96
Tipo de conexión - Connection type		38	38	42	42	44	44	44
Conexión tubo líquido - Liquid line pipe	Ø mm / inch	alocadado - 1/4" g.t.r.	alocadado - 1/4" g.t.r.	alocadado - 1/4" g.t.r.	alocadado	alocadado - 1/4" g.t.r.	alocadado - 1/4" g.t.r.	alocadado - 1/4" g.t.r.
Conexión tubo gas - Gas line pipe	Ø mm / inch	9,53 - 3/8"	9,53 - 3/8"	9,53 - 3/8"	9,53 - 3/8"	9,53 - 3/8"	9,53 - 3/8"	9,53 - 3/8"
Peso neto - Net weight	kg	19,10 - 3/4"	19,10 - 3/4"	19,10 - 3/4"	19,10 - 3/4"	19,10 - 3/4"	19,10 - 3/4"	19,10 - 3/4"
Dimensiones - Dimensions	V/hp - Vh/d mm	37	46	47	47	60	60	60
Dimensiones - Dimensions	V/hp - Vh/d mm	1000/298/800	1000/298/800	1000/298/800	1000/298/800	1350/298/800	1350/298/800	1350/298/800

**CONDICIONES DE PRUEBA - TEST CONDITIONS**

Capacidad Frigorífica\*: Temp. Externa 35°C / Interna 27°C B.S./19°C B.U.  
Cooling Capacity\*: External Temp. 35°C / Internal 27°C D.B. / 19°C W.B.

Capacidad calorífica\*\*: Temp. Interna 21°C / Externa 7°C B.S./6°C B.U.  
Heating Capacity\*\*: Internal Temp. 21°C / External 7°C D.B. / 6°C W.B.