

Cassette de agua

Cassette fan coil

XIDEKO
air for life



CE

digital scroll compressor

Modelo / Model		CCW 2066
Código SAP - SAP code		190000830
Alimentación - Power supply	V/Hz/Ph	220/50/1
Capacidad Frigorífica - Cooling capacity	kW	6,5
Capacidad calorífica - Heating capacity	kW	11,5
Absorción de potencia - Power input	W	106
Nivel sonoro - Sound level	dB (A)	40
Caudal de aire - Air flow volume	m³/h	1020
Velocidad del ventilador - Fan speed	r/min	3
Caudal de agua - Water flow volume	L/h	1265
Pérdida de carga - Water resistant loss	kPa	16,4
Conexión tubos - Pipeline diameter	Ø inch	3/4"
Conexión condensación - Drain pipe connector	Ø inch	3/4"
Tipo conexión - Connector type		hidraulica / hydraulic
Peso unidad interior - Indoor unit weight	kg	62
Dimensiones cuerpo - Dimensions structure	VxPp - Vh/d mm	1160/655/320
Dimensiones panel - Panel dimensions	VxPp - Vh/d mm	1220/690/50

CONDICIONES DE PRUEBA - TEST CONDITIONS

Modalità raffredd.: Ambiente 27°C BS/ 19,5°C BU; Acqua in entrata 7°C; Acqua in uscita 12°C
Cooling Mode: Air conditions 27°C DB/ 19,5°C WB; Inlet water 7°C; Outlet water 12°C

Modalità riscald.: Ambiente 20°C BS; Acqua in entrata 70°C; Acqua in uscita 60°C
Heating Mode: Air conditions 20°C DB; Inlet water 70°C; Outlet water 60°C