



Refrigerador de agua

Water Chiller

XIDEKO
air for life



Mod. 5,2/10 kW



Mod. 12 kW

Kit hidráulico completo- Integrated hydraulic Kit

- Bomba • Vaso de expansión • Depósito • Valvula de seguridad • interruptor fluxométrico •
- pump • expansion vessel • water tank • safety valve • pumpwater flow switch •



Modelo / Model		CRA-5.2P1RB6-B	CRA-10P1RB6-B	CRA-12P1RB6-AA
Código SAP - SAP code		190005292	190005293	190005291
Alimentación - Power supply	V/Hz/Ph	220/50/1	220/50/1	220/50/1
Capacidad frigorífica - Cooling capacity	kW	5,2	10	12
Absorción de potencia - Power input	W	1,85	3,7	4,2
Capacidad calorífica - Heating capacity	kW	5,5	11	13,5
Absorción de potencia - Power input	W	1,8	3,8	4,3
Corriente de arranque - Running current (cool/heal)	A	8,4 - 8,2	12,2 - 12,7	7,5 - 8,0
Caudal de agua - Water flow volume	m³/h	0,9	1,7	2,3
Pérdida de carga - Water resistant loss	Kpa	17	29	32,5
Prevalencia útil - Available pressure	Kpa	60	80	100
Potencia nominal bomba - power input	kW	0,1	0,2	0,6
Capacidad del serbatoio - Tank volume	Lt	23	23	32
Caudal de aire - Air flow volume	m³/h	2200	2200	4000
Motor del ventilador - Fan motor input	W	75	125	200
Nivel sonoro - Sound level	dB (A)	54	56	59
Dimensiones - Overall dimensions	V/hp - Vh/d mm	1110/470/650	1110/470/850	650/650/880
Peso total - Total weight	kg	90	120	150
Refrigerante - Refrigerant	tipo - type	R407C	R407C	R407C
Tubos entrada/salida - Water inlet/outlet	Ø mm	3/4	1"	1"
Valvula de seguridad - Safety valve setting	bar	3	3	3