



Climatizador modular SVD
SVD modular air conditioner
| SVD-33.5M3RC8 |



Climatizador modular SVD
SVD modular air conditioner
| SVD-45M3RC8 |



Configuraciones
Configurations



Modelo / Model		SVD-33.5M3RC8	SVD-45M3RC8
Código SAP - SAP code		190006034	190006035
Alimentación - Power supply	V/Hz/Ph	380/50/3	380/50/3
Capacidad frigorífica - Cooling capacity	kW/BTU/F	33.5-114300-28575	45-153500-38375
Absorción de potencia - Power input	W	9.68	12.86
Capacidad calorífica - Heating capacity	kW/BTU/F	35-119400-29850	47-160400-40100
Absorción de potencia - Power input	W	9.12	12.08
Intensidad de funcionamiento frío/calor - Operating current cool/heat	A	17,3 / 16,4	23,0 / 21,4
Corriente de arranque - Starting current	A	12,7+11,8	12,7+11,8x2
Caudal de aire - Air flow	m³/h	11500/9000	14800/9600
Nivel sonoro - Sound level	dB (A)	58	60
Compresor - Compressor		Digital scroll	Digital scroll
Dimensiones - Overall dimension	l/h/p - l/h/d mm	980/1630/800	1380/1630/830
Peso neto - Net weight	kg	290	382
Conexión tubo Líquido - Liquid line pipe	Ø mm / inch	12.7	15.9
Conexión tubo Gas - Gas line pipe	Ø mm / inch	25.4	35
Largo máx. tubos - Maximum length for one pipe	m	175	175
Desnivel máximo entre unidades - Max. difference in height between the units		15	15

CONDICIONES DE PRUEBA: - TEST CONDITIONS: Capacidad Frigorífica*: Temp. Exterior 35°C / Interior 27°C b.s./19°C b. Cooling Capacity*: External Temp. 35°C / Internal 27°C d.b. / 19°C w.b. • Capacidad Calorífica*: Temp. Interior 21°C / Exterior 7°C b.s./6°C b.u. Heating Capacity*: Internal Temp. 21°C / External 7°C d.b. / 6°C w.b.