

Monosplit "Albus" | "Albus" Wall mounted type



Climatizzatore monosplit Single-split wall mounted type

- | SPDE-2.6GR1RC8-W |
- | SPDE-3.5GR1RC8-W |
- | SPDE-5.3GR1RC8-W |



Climatizzatore dualsplit Multi-split wall mounted type

- | SPDE-2.6+3.5GR1RC8-D-W |



Modello / Model		SPDE-2.6GR1RC8-W	SPDE-3.5GR1RC8-W	SPDE-5.3GR1RC8-W	SPDE-2.6+3.5GR1RC8-D-W
Codice SAP - SAP code		190005966	190005971	190005976	190005981
Alimentazione elettrica - Power supply	V/Hz/Ph	220-240,50,1	220-240,50,1	220-240,50,1	220-240,50,1
Potenza frigorifera - Cooling capacity	kW/BTU/F	2.6-8900-2550	3.5-12000-3400	5.3-18000-5200	2.6+3.5-8900+12000-2550+3400
Potenza assorbita - Power input	W	809	1090	1640	2026
Corrente elettrica assorbita - Operating current	A	5	7	11.3	12
EER - EER	W/W	3.21	3.21	3.23	3.0
Potenza riscaldamento - Heating capacity	kW/BTU/F	2.8-9600-2750	3.8-13000-3700	5.6-19100-5500	2.8+3.8-9600+13000-2750+3700
Potenza assorbita - Power input	W	775	1052	1675	1935
Corrente elettrica assorbita - Operating current	A	4.5	6.5	11.3	11.5
COP - COP	W/W	3.61	3.61	3.40	3.41
Corrente di avviamento - Starting current	A	18	32	40	19/27
Unità interna - Indoor unit					
Portata d'aria - Airflow	m ³ /h	480	520	780	480+520
Umidità rimossa - Moisture removal	L/h	0.8	1.2	1.8	3.5
Potenza assorbita dal ventilatore - Fan motor power supply	W	10	10	20	10
Livello sonoro - Sound level	max/med/min - hi/ni/lo dB (A)	37/35/31/27	39/35/30/27	45/38/36/33	37/35/31/27 - 39/35/30/27
Dimensioni - Overall dimensions	l/h/p - l/h/d mm	815x267x165	815x280x215	960x300x195	815x267x165 - 872x283x178
Peso netto - Net weight	kg	10	11	13	10 - 13
Unità esterna - Outdoor unit					
Portata d'aria - Airflow	m ³ /h	1500	1500	2500	5000
Compressore - Compressor		rotativo - rotary	rotativo - rotary	rotativo - rotary	rotativo - rotary
Qtà refrigerante - Refrigerant qty	gr	730	1100	1620	0.9 - 1.15
Carica aggiuntiva - Additional charge	g/m	30	30	30	30
Livello sonoro - Sound level	dB (A)	50	52	54	60
Dimensioni - Overall dimension	l/h/p - l/h/d mm	848x540x320	848/540/320	926x685x378	950x420x700
Peso netto - Net weight	kg	26	40	56	65
Tubazioni linea Liquido - Liquid line pipe	Ø mm / inch	6,35 - (1/4)	6,35 - (1/4)	6,35 - (1/4)	6,35 - (1/4) - 6,35 - (1/4)
Tubazioni linea Gas - Gas line pipe	Ø mm / inch	9,52 - (3/8)	12,7 - (1/2)	12,7 - (1/2)	9,52 - (3/8) - 12,7 - (1/2)
Max lunghezza tubazioni - Maximum pipe length	m	20	20	20	20
Max dislivello fra le unità - Max. difference in height between the units	m	10	10	15	15

CONDIZIONI DI PROVA - TEST CONDITIONS: Capacità Frigorifera*: Temp. Esterna 35°C / Interna 27°C bs./19°C bu. (Cooling Capacity): Temp. Esterna 35°C / Interna 27°C bs./19°C bu. • Capacità Riscaldamento*: Temp. Interna 21°C / Esterna 7°C bs./6°C bu. (Heating Capacity): Temp. Interna 21°C / Esterna 7°C bs./6°C bu.



il clima residenziale Xideko® | Xideko® residential range