



Monosplit "Clavus" | "Clavus" Wall mounted type



Climatizzatore monosplit Single-split wall mounted type

| SPDE-2.6GR1RC8-R |
| SPDE-3.5GR1RC8-R |



Climatizzatore dualsplit Multi-split wall mounted type

| SPDE-2.6+3.5GR1RC8-D-R |



| Modello / Model | | SPDE-2.6GR1RC8-R | SPDE-3.5GR1RC8-R | SPDE-2.6+3.5GR1RC8-D-R |
|--|--------------------------------|-------------------|-------------------|---------------------------------|
| Codice SAP - SAP code | | 190005969 | 190005974 | 190005985 |
| Alimentazione elettrica - Power supply | V/Hz/Ph | 220-240,50,1 | 220-240,50,1 | 220-240,50,1 |
| Potenza frigorifera - Cooling capacity | kW/BTU/F | 2.6-8900-2550 | 3.5-12000-3400 | 2.6+3.5-8900+12000-2550+3400 |
| Potenza assorbita - Power input | W | 809 | 1090 | 2026 |
| Corrente elettrica assorbita - Operating current | A | 5 | 7 | 12 |
| EER - EER | W/W | 3,21 | 3,21 | 3,01 |
| Potenza riscaldamento - Heating capacity | kW/BTU/F | 2.8-9600-2750 | 3.8-13000-3700 | 2.8+3.8-9600+13000-2750+3700 |
| Potenza assorbita - Power input | W | 775 | 1052 | 1935 |
| Corrente elettrica assorbita - Operating current | A | 4.5 | 6.5 | 11.5 |
| COP - COP | W/W | 3.61 | 3.61 | 3.41 |
| Corrente di avviamento - Starting current | A | 18 | 32 | 19/27 |
| Unità interna - Indoor unit | | | | |
| Portata d'aria - Airflow | m³/h | 480 | 520 | 480+520 |
| Umidità rimossa - Moisture removal | L/h | 0.8 | 1,2 | 3.5 |
| Potenza assorbita dal ventilatore - Fan motor power supply | W | 10 | 10 | 10 |
| Livello sonoro - Sound level | max/med/min - h/h/ni/lo dB (A) | 37/35/31/27 | 39/35/30/27 | 37/35/31/27 - 39/35/30/27 |
| Dimensioni - Overall dimensions | l/h/p - l/h/d mm | 815x267x165 | 815x280x215 | 815x267x165 - 872x283x178 |
| Peso netto - Net weight | kg | 10 | 11 | 10 - 13 |
| Unità esterna - Outdoor unit | | | | |
| Portata d'aria - Airflow | m³/h | 1500 | 1500 | 5000 |
| Compressore - Compressor | | rotativo - rotary | rotativo - rotary | rotativo - rotary |
| Qtà refrigerante - Refrigerant qty | gr | 730 | 1100 | 0.9 - 1.15 |
| Carica aggiuntiva - Additional charge | g/m | 30 | 30 | 30 |
| Livello sonoro - Sound level | dB (A) | 50 | 52 | 60 |
| Dimensioni - Overall dimension | l/h/p - l/h/d mm | 848x540x320 | 848/540/320 | 950x420x700 |
| Peso netto - Net weight | kg | 26 | 40 | 65 |
| Tubazioni linea Liquido - Liquid line pipe | Ø mm / inch | Ø 6,35 - (1/4) | Ø 6,35 - (1/4) | Ø 6,35 - (1/4) - Ø 6,35 - (1/4) |
| Tubazioni linea Gas - Gas line pipe | Ø mm / inch | Ø 9,52 - (3/8) | Ø 12,7 - (1/2) | Ø 9,52 - (3/8) - Ø 12,7 - (1/2) |
| Max lunghezza tubazioni - Maximum pipe length | m | 20 | 20 | 20 |
| Max dislivello fra le unità - Max. difference in height between the units | m | 10 | 10 | 15 |

CONDIZIONI DI PROVA - TEST CONDITIONS: • Capacità Frigorifera*: Temp. Esterna 35°C / Interna 27°C bs./19°C bu./Cooling Capacity*: External Temp. 35°C / Internal 27°C b.s. / 19°C w.b. • Capacità Riscaldamento*: Temp. Interna 21°C / Esterna 7°C bs./6°C bu. / Heating Capacity*: Internal Temp. 21°C / External 7°C b.s. / 6°C w.b.