



Monosplit Inverter "Gaius" | "Gaius" Wall mounted type inverter



Climatizzatore monosplit
Single-split wall mounted type

I SPDE-2.6GR1RC8-INV I
I SPDE-3.5GR1RC8-INV I



Climatizzatore dualsplit
Multi-split wall mounted type

I SPDE-2.6+3.5GR2RC8-DINV I



Modello / Model	SPDE-2.6GR1RC8-INV	SPDE-3.5GR1RC8-INV	SPDE-2.6+3.5GR1RC8-D-INV
Codice SAP - SAP code	190005988	190005991	190005994
Alimentazione elettrica - Power supply	220-240,50,1	220-240,50,1	220-240,50,1
Potenza frigorifera - Cooling capacity	3.3/2.6-11300/8900-3200/2550	4/3.5-13600/12000-3900/3400	2.7/3.6-9200/12300-2650/3500
Potenza assorbita - Power input	1200/600	1400/1000	1960
Corrente elettrica assorbita - Operating current	5.5	6	8.5
EER - EER	4.25	3.45	3.21
Potenza riscaldamento - Heating capacity	3.8/2.85-13000/9700-3700/2800	4.1/3.85-14000/13000-4000/3800	3.1/4.1-10600/14000-3000/4000
Potenza assorbita - Power input	1250/650	1450/1130	1990
Corrente elettrica assorbita - Operating current	6	6.3	8.7
COP - COP	4.22	3.41	3.62
Corrente di avviamento - Starting current	33	33	32
Unità interna - Indoor unit			
Portata d'aria - Airflow	450	450	1250 - 1350
Umidità rimossa - Moisture removal	0.8	1.2	3.5
Potenza assorbita dal ventilatore - Fan motor power supply	10	10	10
Livello sonoro - Sound level	max/med/min - h/mi/lo	42/38/30/28	38/35/32/29 - 40/35/33/30
Dimensioni - Overall dimensions	l/h/p - l/h/d	872/178/283	Unit 2.6 (815X267X165) / Unit 3.5 (872X283X178)
Peso netto - Net weight	12	12	10/11
Unità esterna - Outdoor unit			
Portata d'aria - Airflow	1800	2200	5000
Compressore - Compressor	Twin- rotary	Twin- rotary	Rotary-inverter
Qtà refrigerante - Refrigerant qty	1100	1350	R410a 2.4 Kg
Carica aggiuntiva - Additional charge	15	15	30
Livello sonoro - Sound level	54	54	58
Dimensioni - Overall dimension	l/h/p - l/h/d	848x320x540	950x840x420
Peso netto - Net weight	40	40	72
Tubazioni linea Liquido - Liquid line pipe	Ø mm / inch	6 - (1/4)	6,35 (1/4) - 6,35 (1/4)
Tubazioni linea Gas - Gas line pipe	Ø mm / inch	9,52 - (3/8)	9,53 (3/8) - 12,7 (1/2)
Max lunghezza tubazioni - Maximum pipe length	15	15	20
Max dislivello fra le unità - Max. difference in height between the units	5	5	15

CONDIZIONI DI PROVA - TEST CONDITIONS: • Capacità Frigorifera*: Temp. Esterna 35°C / Interna 27°C bs./19°C bu / Cooling Capacity*: External Temp. 35°C / Internal 27°C b.s. / 19°C w.b. • Capacità Riscaldamento*: Temp. Interna 21°C / Esterna 7°C bs./6°C bu. - Heating Capacity*: Internal Temp. 21°C / External 7°C b.s. / 6°C w.b.