


Climatizzatore pavimento/soffitto | Floor/ceiling type



Climatizzatore Pavimento/soffitto Floor/ceiling type

I SXDE-5.3M1RC7 I
I SXDE-7.0M1RC7 I



Climatizzatore Pavimento/soffitto Floor/ceiling type

I SXDE-10.6M1RC7 I
I SXDE-14.1M1RC7 I



Modello / Model		SXDE-5.3M1RC7M	SXDE-7.0M1RC7	SXDE-10.6M1RC7	SXDE-14.1M1RC7
Codice SAP - SAP code		190005550	190005551	190005552	190005553
Alimentazione elettrica - Power supply	V/Hz/Ph	220-240,50,1	220-240,50,1	380,50,3	380,50,3
Potenza frigorifera - Cooling capacity	kW/BTU/F	5.4-18500-5300	7.1-240007000	10.5-36000-1030	14-48000-14000
Potenza assorbita - Power input	W	1900	2600	3800	4900
Corrente elettrica assorbita - Operating current	A	10	14	8.8	10.3
EER - EER	W/W	2.84	2.73	2.76	2.85
Potenza riscaldamento - Heating capacity	kW/BTU/F	6-20500-6000	8-27300-8000	11.1-38000-10900	15.5-53000-15100
Potenza assorbita - Power input	W	2600	3300	5200	6100
Corrente elettrica assorbita - Operating current	A	8.5	12.1	6.4	8.2
COP - COP	W/W	2.30	2.42	2.13	2.54
Corrente di avviamento - Starting current	A	36.8	61	61	66
Unità interna - Indoor unit					
Portata d'aria - Air flow	m³/h	800/600/500	1200/900/700	1600/1200/1000	2000/1800/1600
Umidità rimossa - Moisture removal	L/h	1.8	2.4	3.8	4.8
Potenza assorbita dal ventilatore - Fan motor power supply	W	115/95/78	115/95/78	134/118/107	89.5/81.5/77.5
Livello sonoro - Sound level	max/med/min - hi/ni/lo dB (A)	38	40	41	58
Dimensioni - Overall dimensions	l/h/p - l/h/d mm	995X660x198	995X660x198	1285x660x198	1670x680x240
Peso netto - Net weight	kg	27	27	35	52
Unità esterna - Outdoor unit					
Portata d'aria - Airflow	m³/h	2400	3000	5000	6000
Compressore - Compressor		Rotary	Rotary	Scroll	Scroll
Qtà refrigerante - Refrigerant qty	gr	R410a 2000	R410a 2600	R410a 3000	R410a 3700
Carica aggiuntiva - Additional charge	g/m	30	30	35	35
Livello sonoro - Sound level	dB (A)	48	55	57	58
Dimensioni - Overall dimension	l/h/p - l/h/d mm	845x695x335	895x860x330	990x960x360	940x1245x340
Peso netto - Net weight	kg	53	67	101	108
Tubazioni linea Liquido - Liquid line pipe	Ø mm / inch	6.35 - (1/4)	9.53 - (3/8)	9.53 - (3/8)	9.53 - (3/8)
Tubazioni linea Gas - Gas line pipe	Ø mm / inch	12.7 - (1/2)	16 - (5/8)	16 - (5/8)	16 - (5/8)
Max lunghezza tubazioni - Maximum pipe length	m	25	30	30	50
Max dislivello fra le unità - Max. difference in height between the units	m	15	15	20	30

CONDIZIONI DI PROVA - TEST CONDITIONS: Capacità Frigorifera*: Temp. Esterna 35°C / Interna 27°C b.s./19°C b.u. Cooling Capacity*: External Temp. 35°C / Internal 27°C b.s./19°C b.u. • Capacità Riscaldamento*: Temp. Interna 21°C / Esterna 7°C b.s./6°C b.u. Heating Capacity*: Internal Temp. 21°C / External 7°C b.s./6°C b.u.

